

**DEL1316**





**General Feature**

- ★ Dimensions: 160L x 25W x 31D mm
- ★ DEL1316/DEL1316F Fail Secure/Fail Safe
- ★ Current: 400mA/12VDC, (F)200mA/12VDC  
200mA/24VDC, (F)100mA/24VDC
- ★ Face Plates:  
DEL1316(F) - Steel (Painted)  
SDEL1316(F) - Stainless steel
- ★ Keep Depth: 9.6mm


**DEL1316 INSTALLATION**

Metal or Aluminium door frame



Dimensions needed to install strike  
Unit:mm

Wooden door frame



**DEL1316(J.A.B)**



**General Feature**

- ★ DEL1316J – Steel face plate, Adjustable symmetrical strike, fail secure, 12VDC
- ★ DEL1316JA – Stainless steel face plate, Adjustable symmetrical strike, w/day locking lever, fail secure, 12VDC
- ★ DEL1316JAB-24 – Steel face plate, Adjustable symmetrical strike, w/day locking lever and impulse switch, fail secure, 24VDC
- ★ Fail safe type: DEL1316JF/SDEL1316JF only.
- ★ Dimensions:  
DEL1316J/SDEL1316J - 160L x 25W x 31.4H mm
- ★ Voltage: 12VDC(default) or 24VDC
- ★ Current draw:  
600mA/12VDC, 300mA/24VDC (fail secure)  
280mA/12VDC, 140mA/24VDC (fail safe)
- ★ Face plate:  
aluminum - 160L x 25W x 2.8T mm  
stainless steel - 160L x 25W x 2.8T mm
- ★ Keeper depth: 6mm
- ★ Applicable door latch: 9 mm

**INSTALLATION**

