



Commercial Grade 2 Auxiliary Locksets



5200 series-DB

5201DB Single cylinder
5202DB Double cylinder
5212DB Classroom



5200IC series-DB

5201ICDB Single cylinder
5202ICDB Double cylinder
5212ICDB Classroom




Specification

Door Thickness	1-3/8" to 1-3/4"(35~45mm) Standard, 5200IC series (40~51mm)
Door Prep	Backset- 2-3/8" or 2-3/4" (60 or 70mm)
Cylinder	Brass, 6 pin
Keyway	Schlage C keyway on standard cylinders. Best A keyway on I/C core cylinders.
Deadbolt	1" throw dead bolt with hardened steel saw-resistant roller in deadbolt
Front	1-1/8" x 2-1/4" square or round corner faceplate. Optional 1" x 2-1/4" square or round corner latch front available.
Strike	1-1/8" x 2-3/4" square corner strike plate & strike frame reinforcer.
Finish	US26D 、US32D 、US3 、US10B 、US32

Compliance

ANSI	Meets ANSI/BHMA A156.36 Grade 2
UL	3 hours fire rating

Functions

Code	Function	Description	ANSI No.
1		Single Cylinder Deadlock with Thumb Turn Deadbolt thrown or retracted by key or by Thumb Turn Bolt automatically deadlocks when fully thrown	E0152
2		Double Cylinder Deadlock Deadbolt thrown or retracted by key from either side Bolt automatically deadlocks when fully thrown	E0142
12		Single Cylinder Deadlock with Thumb Turn Deadbolt thrown or retracted by key Thumb Turn retracts deadbolt but not project it. Bolt automatically deadlocks when fully thrown	E0172